

Technical Data Sheet | CH-L5F2PG16K

LithiumVault FirePro® Cabinet with Control Panel & Charging | 2-Door | Tall

Cabinet designed for storing and charging lithium-ion batteries with fire safety features certified for 90-minutes of fire protection, according to EN 14470-1 TYPE 90 standard.

Product Specifications

External Dimensions (WxDxH)	1200 x 600 x 2050mm
Internal Dimensions (WxDxH)	1095 x 446 x 1540mm
Shelf Dimensions (WxDxH)	1094 x 420 x 39mm
Number of Shelves	4 x perforated shelves
Shelf Load Capacity	80kg
Doors (Door Locks)	2 (2 with 4 x keys supplied)
Charging Points	24 (4 x power sockets)
Tare Weight	350kg (empty cabinets, excl. accessories)
Power Socket	Standard Regional Socket
Power Phase	Single
Cable Section	2m 3G2.5mm ²
Max Amp. Output	10A
Voltage	230V
Max Output	2,300W



Product Features and Benefits

- 90-Minutes Fire Rated
- Steel Construction
- Anti-spark hinges
- Ventilation
- Self-closing door system
- Charging sockets with illuminated on/off safety switch
- FirePro® fire detection and automatic extinguishing system with FPC-2V2 control panel
- Sounder beacon
- Smoke and heat sensors
- LPCB Certified to EN 12094-1 and EN 54-2 and 4 and EN 14470-1 TYPE 90
- Spill tray