



BS1943E



BS1946K



BS1945

The **BATTERY COMMANDER PRO SERIES** is certified to VDMA 24994:2024-08 standard by ECB.S and constructed to safeguard both lives and property from the potentially catastrophic consequences of Lithium battery fires. Providing a secure storage and charging solution tailored for Lithium-Ion batteries, these units mitigate the myriad of risks posed by such batteries, including thermal runaway due to temperature fluctuations, impact, or manufacturing defects. Such hazards can lead to spontaneous ignition and formidable fire outbreaks, that pose significant challenges for extinguishment.

The Battery Commander Pro Series ensures peace of mind through its sturdy double-wall construction, certified for fire resistance, impact resistance, and security. UK Police approved (Secured By Design scheme).

Customers can select from six size options, each offering either key or electronic locking mechanisms, integrated smoke detectors, reinforced insulated shelving, and built-in power outlets. Furthermore, this range includes a plinth for effortless relocation and removal from the premises in case of a fire emergency.

FEATURES

- VDMA 24994:2024-08 Certified
- Large volume Lithium-Ion battery storage & charging
- Storage and charging for up to 22,500Wh of batteries
- Robust Safe construction
- Key or electronic locking
- Internal temperature monitor as standard
- Reinforced and Insulated shelving
- Full electronic monitoring system

MODEL NUMBER	LOCKING OPTIONS	EXTERNAL DIMENSIONS H x W x D	SHELF CAPACITY	MAX. BATTERY CAPACITY	INTERNAL DIMENSIONS H x W x D	DOOR SWING/ HANDLE DEPTH	WEIGHT	CAPACITY	PDUs	SHELVES	DOORS
BS1941 [†]	K/E/F	855 x 690 x 710mm	2500Wh	2500Wh	450 x 510 x 400mm	650 / 40mm	185kg	91 Litres	1x (4 Gang)	0	1
BS1942 [†]	K/E/F	995 x 690 x 710mm	2500wh	5000Wh	590 x 510 x 400mm,	650 / 40mm	213kg	120 Litres	2x (4 Gang)	1	1
BS1943	K/E/F	1385 x 690 x 710mm	2500Wh	7500Wh	980 x 510 x 400mm,	650 / 40mm	261kg	199 Litres	3x (4 Gang)	2	1
BS1944 [†]	K/E/F	1610 x 690 x 710mm	2500Wh	10000Wh	1205 x 510 x 400mm	650 / 40mm	388kg	245 Litres	3x (4 Gang)	3	1
BS1945	K/E/F	1910 x 690 x 710mm	2500Wh	12500Wh	1505 x 510 x 400mm	650 / 40mm	416kg	307 Litres	5x (4 Gang)	4	1
BS1946	K/E/F	1910 x 1125 x 710mm	4500Wh	22500Wh	1505 x 945 x 400mm	560 / 40mm	610kg	569 Litres	5x (8 Gang)	4	2

* As tested in base model. [†]Only available as factory order with MOQ.

This information is provided as a guide only. All weights are for the product only and does not include the packaging.



SPECIFICATIONS

- **SUITABLE FOR** – The storage and charging of all Lithium Ion batteries up 25kgs, such as – power tools, garden tools, e-bikes/scooters, drones, laptop, mobile phone. Maximum storage capacities are listed in the table.
- **FIRE PROTECTION (INSIDE TO OUTSIDE)** – VDMA 24994:2024-08 Certified for a maximum shelf capacity of 2500Wh (BS1941-BS1945) to 4500Wh (BS1946) and total capacity from 2500Wh (BS1941) to 22500Wh (BS1946). See table for detailed capacity per model.
- **FIRE PROTECTION (OUTSIDE TO INSIDE)** – Factory tested to EN 14470-1 – Fire protection for 90 minutes from outside to in. NT Fire 017-120p certified – Fire protection for 120 minutes from outside to in.*
- **DROP TEST** – Fire and impact tested from 9.1 metres for resistance to the impact of falling through the burning floors of a building.
- **CHARGING** – Safely charge your Lithium batteries using the fitted power points – see table for details, with the option to add further PDUs to the pre-wired control box. Always check with your electrician to be sure not to overload your 13amp mains supply. Further 13 AMP Mains Supply or Three Phase can be added (POA).
- **VENTILATION** – Fitted as standard with air exhaust duct, for added ventilation. Dedicated ducting to the outside is also strongly recommended for the most secure and safe extraction in the event of thermal runaway.
- **SHELVING** – Supplied with reinforced and insulated height adjustable shelves capable of carrying 100kg at a time.

ELECTRONIC MONITORING AND CONTROL UNIT

- **INTERNAL TEMPERATURE MONITOR** – For safety, the cabinet comes as standard with an external temperature warning lamp, that gives an early warning of a potential issue with a battery overheating. In the event of excessive heat inside the cabinet, the control unit immediately cuts power to chargers and sounds an alarm.
- **DOOR ALARM** – The doors are fitted with sensors to prevent the doors being left open. A buzzer will sound to warn you.

OPTIONAL FEATURES

- **SP Safe Monitor**
For enhanced safety, the cabinet can be fitted with internal temperature and humidity monitor, that links to a mobile phone App and alerts you if the maximum set temperature is breached.
- **Fire Suppression**
Specially formulated condensed aerosol fire extinguishing for rapid and effective fire suppression, specifically designed for Lithium Ion batteries.

FirePro.

